

Safety Data Sheet

Ether, Anhydrous, Absolute, ACS

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Ether, Anhydrous, Absolute, ACS

Synonyms/Generic Names: Ether, Ethyl Ether, Ethyl Oxide, Diethyl Oxide

Product Number: 2035

Product Use: Industrial, Manufacturing or Laboratory use

Manufacturer: Columbus Chemical Industries, Inc.

N4335 Temkin Rd. Columbus, WI. 53925

For More Information Call: 920-623-2140 (Monday-Friday 8:00-4:30)

In Case of Emergency Call: CHEMTREC - 800-424-9300 or 703-527-3887 (24 Hours/Day, 7 Days/Week)

2. HAZARDS IDENTIFICATION

OSHA Hazards: Flammable liquid, Target organ effect, Irritant, Harmful by ingestion

Target Organs: Central nervous system

Signal Words: Danger

Pictograms:



GHS Classification:

Flammable liquids	Category 1
Acute toxicity, Oral	Category 4
Eye irritation	Category 2A
Specific target organ toxicity-single exposure	Category 3

GHS Label Elements, including precautionary statements:

Hazard Statements:

H224	Extremely flammable liquid and vapor.	
H302	Harmful if swallowed.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	

Precautionary Statements:

P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.

Revised on 02/04/2015 Page 1 of 6

P240	Ground/Bond container and receiving equipment.		
P241	Use explosion-proof electrical/ventilating/lighting/equipment.		
P242	Use only non-sparking tools.		
P243	Take precautionary measures against static discharge.		
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.		
P264	Wash hands thoroughly after handling.		
P270	Do not eat, drink or smoke when using this product.		
P271	Use only outdoors or in a well-ventilated area.		
P280	Wear protective gloves/protective clothing/eye protection/face protection.		
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician if you feel unwell.		
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse		
F 303+F 301+F 333	skin with water/shower.		
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact		
1 303+1 331+1 330	lenses, if present and easy to do. Continue rinsing.		
P312	Call a POISON CENTER/doctor/physician if you feel unwell.		
P330	Rinse mouth.		
P337+P313	If eye irritation persists: Get medical advice/attention.		
P370+P378	In case of fire: Use appropriate media to extinguish.		
P403+P235	Store in a well-ventilated place. Keep cool.		
P405	Store locked up.		
P501	Dispose of contents/container in accordance with local regulations.		

Potential Health Effects

Eyes	Causes eye irritation.
Inhalation	May be harmful if inhaled. Causes respiratory tract irritation. Vapors may cause drowsiness and dizziness.
Skin	May be harmful if absorbed through skin. Causes skin irritation.
Ingestion	Harmful if swallowed.

NFPA Ratings

Health	2
Flammability	4
Reactivity	0
Specific hazard	Not Available

HMIS Ratings

Health	2	
Fire	4	
Reactivity	0	
Personal	Н	

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight %	CAS#	EINECS# / ELINCS#	Formula	Molecular Weight
Diethyl Ether	>98	60-29-7	200-467-2	C ₄ H ₁₀ O	74.12 g/mol
Ethanol	≤2	64-17-5	200-578-6	C ₂ H ₆ O	46.07 g/mol

4. FIRST-AID MEASURES

Eyes	Rinse with plenty of water for at least 15 minutes and seek medical attention immediately.		
Inhalation	Move casualty to fresh air and keep at rest. If breathing is difficult, give oxygen. If not		
	breathing, give artificial respiration. Get medical attention immediately.		
Skin	Flush with plenty of water for at least 15 minutes while removing contaminated clothing and		
	wash using soap. Get medical attention.		
Ingestion	Do Not Induce Vomiting! Never give anything by mouth to an unconscious person. If		
	conscious, wash out mouth with water. Get medical attention.		

Revised on 02/04/2015 Page 2 of 6

5. FIRE-FIGHTING MEASURES

Suitable (and unsuitable)	Flammable liquid. For small (incipient) fires, use media such as		
extinguishing media	"alcohol" foam, dry chemical, or carbon dioxide. For large fires, apply		
	water from as far as possible. Use very large quantities (flooding) of		
	water applied as a mist or spray; solid streams or water may be		
	ineffective. Cool all affected containers with water.		
Special protective equipment	Wear self-contained, approved breathing apparatus and full protective		
and precautions for firefighters	clothing, including eye protection and boots		
Specific hazards arising from	Emits toxic fumes (carbon oxides) under fire conditions. See also		
the chemical	Stability and Reactivity section. Vapors can travel to a source of		
	ignition and flash back. Containers may explode in a fire. Cool		
	containers from a distance using water spray. SENSITIVE TO STATIC		
	DISCHARGE.		

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	See section 8 for recommendations on the use of personal protective equipment.
Environmental precautions	Prevent spillage from entering drains. Any release to the environment
	may be subject to federal/national or local reporting requirements.
Methods and materials for	Absorb spill with vermiculite or other noncombustible absorbent material,
containment and cleaning up	then place in a suitable container for disposal. Clean surfaces thoroughly
	with water to remove residual contamination. Dispose of all waste and
	cleanup materials in accordance with regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Use with adequate ventilation and grounding. Wash thoroughly after using. Keep container closed when not in use. Keep away from sources of ignition. No smoking. Take measure to prevent the buildup of electrostatic charge.

Conditions for safe storage, including any incompatibilities

Store in tightly closed, original containers in a cool, dry, well ventilated area. Store between 55-80°F for product stability. Do not store with strong oxidizing agents. Avoid sunlight

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure controls: Ventilation and appropriate grounding of containers.

Component	Exposure Limits	Basis	Entity
Diethyl Ether 400 ppm 1210 mg/m ³		TLV	ACGIH
	500 ppm 1520 mg/m ³	STEL	ACGIH
	400 ppm 1200 mg/m ³	PEL	OSHA
	1900 ppm	IDLH	OSHA

Revised on 02/04/2015 Page 3 of 6

TWA: Time Weighted Average over 8 hours of work. TLV: Threshold Limit Value over 8 hours of work.

REL: Recommended Exposure Limit PEL: Permissible Exposure Limit

STEL: Short Term Exposure Limit during x minutes. IDLH: Immediately Dangerous to Life or Health WEEL: Workplace Environmental Exposure Levels

CEIL: Ceiling

Personal Protection:

Eyes	Wear chemical safety glasses or goggles, and face shield.
Inhalation	Provide local exhaust, preferably mechanical. If exposure levels are excessive, use an approved respirator.
Skin	Wear nitrile or rubber gloves, and full body covering. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Other	Not Available

Other Recommendations

Provide eyewash stations, quick-drench showers and washing facilities accessible to areas of use and handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.)	Clear, colorless liquid
Odor	Mild alcohol
Odor threshold	8.9 ppm
pH	Not Available
Melting point/freezing point	-116°C (177°F)
Initial boiling point and boiling range	35°C (94°F)
Flash point	-45°C (-49°F) (closed Cup
Evaporation rate	Not Available
Flammability (solid, gas)	Flammable
Upper/lower flammability or explosive limit	39%-1.9%
Vapor pressure	440 mmHg at 20°C
Vapor density	2.6
Relative density	0.706 g/mL at 25°C (77°F)
Solubility (ies)	69 g/L
Partition coefficient: n-octanol/water	Not Available
Auto-ignition temperature	160°C (320°F)
Decomposition temperature	Not Available

10. STABILITY AND REACTIVITY

Chemical Stability	Not stable. Prolonged exposure to sunlight and air may form unstable peroxides. Peroxide formation may occur in ether containers that have been opened and remain in storage for more than 6 months. Peroxides can be detonated by friction, impact, or heating.
Possibility of Hazardous Reactions	Will not occur.
Conditions to Avoid	Keep away from heat, flame and sparks.
Incompatible Materials	Oxidizers and strong acids.
Hazardous Decomposition Products	Carbon oxides.

Revised on 02/04/2015 Page 4 of 6

11. TOXICOLOGICAL INFORMATION

Acute Toxicity Diethyl Ether

Skin	Skin – rabbit – 14.2 g/kg
Eyes	Not Available
Respiratory	LC50 Inhalation – mouse – 30 min – 31000 ppm
Ingestion	LD50 Oral – rat – 1215 mg/kg

Carcinogenicity

	- -
IARC	No components of this product present at levels greater than or equal to 0.1% is identified
	as probable, possible or confirmed human carcinogen by IARC.
ACGIH	A3: Confirmed animal carcinogen with unknown relevance to humans. (Ethyl Alcohol)
NTP	No components of this product present at levels greater than or equal to 0.1% is identified
	as a known or anticipated carcinogen by NTP.
OSHA	No components of this product present at levels greater than or equal to 0.1% is identified
	as a carcinogen or potential carcinogen by OSHA.

Signs & Symptoms of Exposure

Eyes	Redness, irritation, tearing.
Inhalation	Coughing, wheezing, irritation of upper respiratory tract.
Skin	Irritation, redness, drying, cracking.
Ingestion	Nausea, vomiting, diarrhea, irritation of gastrointestinal tract.

Chronic Toxicity	Not Available
Teratogenicity	Not Available
Mutagenicity	Not Available
Embryotoxicity	Not Available
Specific Target Organ Toxicity	May cause drowsiness or dizziness.
Reproductive Toxicity	Not Available
Respiratory/Skin Sensitization	Not Available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Diethyl Ether

Aquatic Vertebrate LC50 – Pimephales promelas (fathead minnow) – 2560 mg/l – 96 hours		
Aquatic Invertebrate	rtebrate EC50 - Daphnia magna (Water flea) - 165 mg/l - 24 h	
Algae NOEC - Desmodesmus subspicatus (green algae) - > 100 mg/l - 72 h		

Persistence and Degradability	Not Available
Bioaccumulative Potential	Not Available
Mobility in Soil	Not Available
PBT and vPvB Assessment	Not Available
Other Adverse Effects	Not Available

13. DISPOSAL CONSIDERATIONS

Waste Residues	Users should review their operations in terms of the applicable federal/national or local regulations and consult with appropriate regulatory agencies if necessary before disposing of waste product container or residue.
Product	Users should review their operations in terms of the applicable federal/national or
Containers	local regulations and consult with appropriate regulatory agencies if necessary
	before disposing of waste product container.

Revised on 02/04/2015 Page 5 of 6 The information offered in section 13 is for the product as shipped. Use and/or alterations to the product may significantly change the characteristics of the material and alter the waste classification and proper disposal methods.

14. TRANSPORTATION INFORMATION

US DOT	UN1155, Diethyl Ether, 3, pg I
TDG	UN1155, DIETHYL ETHER, 3, pg I
IMDG	UN1155, DIETHYL ETHER, 3, pg I
Marine Pollutant	No
IATA/ICAO	UN1155, Diethyl Ether, 3, pg l

15. REGULATORY INFORMATION

TSCA Inventory Status	All ingredients are listed on the TSCA inventory.
DSCL (EEC)	All ingredients are listed on the DSCL inventory.
California Proposition 65	Not Listed
SARA 302	Not Listed
SARA 304	Not Listed
SARA 311	Fire Hazard, Acute Health Hazard, Chronic Health Hazard
SARA 312	Fire Hazard, Acute Health Hazard, Chronic Health Hazard
SARA 313	Listed: Diethyl Ether
WHMIS Canada	Class B-2: Flammable and combustible liquid- Flammable liquid

16. OTHER INFORMATION

Revision	Date
Revision 1	07-26-2011
Revision 2	02/04/2015

Disclaimer: Columbus Chemical Industries, Inc. ("Columbus") believes that the information herein is factual but is not intended to be all inclusive. The information relates only to the specific material designated and does not relate to its use in combination with other materials or its use as to any particular process. Because safety standards and regulations are subject to change and because Columbus has no continuing control over the material, those handling, storing or using the material should satisfy themselves that they have current information regarding the particular way the material is handled, stored or used and that the same is done in accordance with federal, state and local law. COLUMBUS MAKES NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING (WITHOUT LIMITATION) WARRANTIES WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN OR WITH RESPECT TO FITNESS FOR ANY PARTICULAR USE.

Revised on 02/04/2015 Page 6 of 6